

DIMENSIONS & DETAILS

Cavity

| | |
|------------------------|--|
| Module Size | 7 ³ / ₄ " W x 7 ³ / ₄ " L x 1 ¹³ / ₁₆ " H (198mm W x 198mm L x 46 mm H) |
| Cable Raceway Capacity | 6" W x 1 ¹³ / ₁₆ " H (152mm W x 46mm H) 196 CAT5e cables per raceway |

System Dead Load

| | |
|--------|---|
| Weight | 6.05 lbs per square foot 29.54 kg per square meter |
|--------|---|

Floor Tiles

| | |
|-----------------|---|
| Tile Size | 24" x 24" (610mm x 610mm) |
| Tile Dimensions | 23 ⁷ / ₈ " W x 23 ⁷ / ₈ " L x ⁷ / ₈ " D (607mm W x 607mm L x 21mm D) |
| Tile Weight | 21.5 lbs (9.75 kgs) each |

Steel Supports

| | |
|---------------------|--|
| Support Height | 2 ⁵ / ₈ " (67mm) to bottom of carpet |
| Floor Cavity Height | 1 ¹³ / ₁₆ " (46mm) base to underside of tile |
| Component Size: | 5 ¹ / ₄ " diameter x 1 ¹¹ / ₁₆ " H (133mm diameter x 43mm H) 4" (102mm) diameter top |

Webbing

| | |
|----------------|--|
| Webbing Size | 24" x 24" (610mm x 610mm) ¹ / ₈ " (2.5mm) thick (typical) |
| Inc. Connector | 36" x 36" (915mm x 915mm) |

Pad Nuts

| | |
|--------------|--|
| Pad Nut Size | 4" diameter x ¹ / ₁₆ " thick (102mm diameter x 1.6mm thick) |
|--------------|--|

Screw & Washer Assembly

| | |
|---------------|--|
| Washer Size | 1 ¹ / ₂ " diameter x ¹ / ₁₆ " thick (38mm diameter x 1.6mm thick) |
| Philips Screw | ¹ / ₄ " x 2" long (6.3mm x 50mm long) |

Perimeter Blocking

| | |
|---------------|---|
| Blocking Size | 2 ⁹ / ₁₆ " H x 1 ¹³ / ₁₆ " W x 19'-0" L (64mm H x 46mm W x 5791mm L) |
|---------------|---|

Perimeter Fasteners

| | |
|---------------|--|
| Philips Screw | ¹ / ₄ " x 2 ¹ / ₄ " long (6.3mm x 57mm long) |
|---------------|--|